


IRA

Reducing Adapter



Male to Female NPT Threads

Part Number	Male Pipe Size	Female Pipe Size	Dimension			Pressure Ratings, psig(bar)	
			A	E	H	SS316, Steel	Brass
IRA - 2N - 4N	1/8	1/4	32.0	4.8	19.1	6600(454)	3300(227)
IRA - 2N - 6N	1/8	3/8	33.8	4.8	22.2	5300(365)	2600(179)
IRA - 4N - 6N	1/4	3/8	38.1	7.1	22.2		
IRA - 2N - 8N	1/8	1/2	40.1	4.8	26.9	4900(337)	2400(165)
IRA - 4N - 8N	1/4	1/2	44.7	7.1	26.9		
IRA - 6N - 8N	3/8	1/2	44.4	9.6	26.9		
IRA - 4N - 12N	1/4	3/4	47.0	7.1	33.3	4600(316)	2300(158)
IRA - 6N - 12N	3/8	3/4	46.2	9.6	33.3		
IRA - 8N - 12N	1/2	3/4	51.3	11.9	33.3		
IRA - 4N - 16N	1/4	1	49.8	7.1	41.2	4400(303)	2200(151)
IRA - 8N - 16N	1/2	1	54.9	11.9	41.2		
IRA - 12N - 16N	3/4	1	55.1	15.7	41.2		

※ ISO Tapered Threads are available upon request.