

Washdown Products

Nozzles

Super Klean

Duraflow High Flow Spray Nozzles

Part #:	Description
*DH150S-DB	High flow DuraFlow 300 series stainless steel nozzle with dark blue cover

*Stock Item



Rating: 150 PSI / 200°F (93°C)

Maximum Tested Operating Pressure of 500 PSI

NOT FOR USE WITH STEAM

Dark Blue

Standard

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
25	2.93
50	3.86
75	4.91
100	5.78
125	6.71
150	7.19

High Flow

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89

*Estimated

Duraflow "MINI" Spray Nozzles

Part #:	Description
DM150S-DB	DuraFlow "Mini" 300 series stainless steel nozzle with dark blue cover



Rating: 150 PSI / 200°F (93°C)

NOT FOR USE WITH STEAM

Dark Blue

Standard

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
25	2.93
50	3.86
75	4.91
100	5.78
125	6.71
150	7.19

High Flow

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89

*Estimated

Standard Nozzles

Part #:	Description
150B-DB	Brass nozzle with dark blue cover
150A-LB	Anodized aluminum nozzle with light blue cover



Rating: 150 PSI / 200°F (93°C)

Maximum Tested Operating Pressure of 500 PSI

NOT FOR USE WITH STEAM

Standard Nozzles

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89
200	12.67

Inlet Pressure *(PSIG)	Flow Rate *(GPM)
250	15.01
300	16.12
350	17.54
400	19.55
450	20.52
500	22.01

*Estimated

Duraflow Nozzle Wand -D-Wand Series

Part #:	Description
D-WAND	300 series stainless steel wand with quick disconnect and adjustable spray tip



: @ALPHAGROUP



: 0-2792-9333



: www.alphagroup.co.th